



## Wood Technical Data Sheet








## WOOD FLOORING



# Wood Technical Information

<b>Product</b>	3-Strip	Plank
<b>Wearlayer thickness (mm)</b>	3.5 ± 0.1	3.0 ± 0.1
<b>Thickness (mm)</b>	14.5	14.0
<b>Width (mm)</b>	190	145 <sup>(1)</sup>
<b>Length (mm)</b>	1820	1820
<b>Boards per pack</b>	6	6
<b>m<sup>2</sup> per pack</b>	2.075	1.583
<b>Moisture content</b>	7% ± 1% / DIN 280	
<b>Surface coating</b>	6 coats of Klumpp Miraphen UV hardened acrylic lacquer satin finish <sup>(2)</sup>	
<b>Formaldehyde emission</b>	E1 / SS2702236	
<b>Locking system</b>	Tongue and groove	
<b>Installation <sup>(3)</sup></b>	Floating / Direct Stick	
<b>Underfloor heating compatible <sup>(4)</sup></b>	Low temperature (max 27°C) water-borne system or self-regulating electrical system	

- (1) Merbau Plank - 140mm
- (2) Except Ash White, Oak White and Oak Brushed Limewash - matt finish
- (3) Refer detailed instructions
- (4) Beech, Kempas and Maple are not recommended for underfloor heating.
- (5) Except Tanned Oak and Oak Brushed Limewash - Uniclic Cliplock.

Colour	Species	3-Strip	Plank
	Ash White <sup>(2)</sup>	x	x
	Beech	x	x
	Blue Gum	x	x
	Cherry	x	o
	Hevea	x	o
	Iroko	x	x
	Jatoba	x	x
	Kempas	x	x
	Maple	x	x
	Merbau	x	x
	Oak Brushed Limewash <sup>(2)(5)</sup>	o	x
	Oak Natural	x	x
	Oak Tanned <sup>(5)</sup>	x	x
	Oak White <sup>(2)</sup>	x	x

The above colours are indicative only. Being a natural product, shade variations are normal. Please check batch/colour variation before installation.

## Brinell Hardness Rating



The higher the Brinell rating, the harder the wood

Distributed exclusively in New Zealand by Jacobsen Creative Surfaces Limited and available only through approved stockists.



www.woodworks.net.nz  
Freephone 0800 527 966

**WOOD FLOORING**